

# LECO 1800E-OHV

The 1800E-OHV cold aerosol ULV generator sets the standard for professional equipment. An 18 Horsepower Briggs & Stratton Over Head Valve (OHV) engine combined with the powerful features you demand make the 1800E-OHV the ideal choice for the big, tough jobs.



The LECO 1800E-OHV is the most widely recognized and dependable heavy duty ULV sprayer in the industry. Top performance and a competitive price make it a perfect choice for professionals in public health programs.

## DISCOVER THE CLARKE ADVANTAGE TODAY:

- WHOPES Approved
- Unmatched craftsmanship
- Easy Parts Ordering
- Strictest quality control
- User friendly operation
- Easy installation

## SPECIFICATIONS

Engine	18 HP (570 cc)
Blower	350 CFM @ 10 P.S.I.
Nozzle	IHPLAT
Flow Rate	ULV 0.53 liter/minute (18 oz)
Formulation Tank	56.7 liter (15 gal)
Flush Tank	3.8 liter (1 gal)
Fuel Tank	45.4 liter (12 gal)
Weight	216 kgs (475 lbs) Dry
Dimensions	121.9 cm x 99 cm x 91.4 cm (LxWxH) (48" x 39" x 36")
Emission Filter	High Vacuum Carb Evaporation Vent



# LECO 1800E-OHV



## STANDARD POWER FEATURES

The 1800E is a great choice for mosquito control, public health and odor control. It features application rates up to 0.53 liters/ minute (18 oz/minute) and all the standard features professionals demand:

- The Industrial High Performance Laminar Air-Flow Technology nozzle swivels 360° horizontally and 200° vertically and is specifically designed for Dengue control programs
- Rotary positive displacements blower 350 CFM@ 10 P.S.I.
- Glycerin filler pressure gauge
- Meets all the label requirements for ground ULV products, including malathion at 32.2 kph (20 mph) rate
- Remote cab flow control
- Non-shear anti-vibration mounts
- FMI electric lab pump, with waterproof, lockable enclosure
- Electric start
- Flush system with 3.8 liter (1 gallon) solution tank
- Lockable pour-clean 56.7 liter (15 gallon) poly chemical tank
- 18 HP OHV Briggs & Stratton engine with automotive type lubrication with spin-on-oil filter
- All steel construction with Z-base rails for easier vehicle mounting
- 45.4 liter (12 gallon) marine poly gas tank with gauge
- Engine hour meter and tachometer
- Two stage powder coat finish on all frame parts

---

**For further information on product please contact:**

**Ms. Puja Kumari**

**UPL Limited**, 3rd Floor, V- Fortune, Plot No. 7A,  
S.V. Road, Santacruz (W), Mumbai-400054, Mumbai.

**P** +91 22 66072346

**M** +91 8879 657809

**E** puja.kumari@uniphos.com

**W** [www.uplonline.com](http://www.uplonline.com)